

**CLAIM AMENDMENTS:**

Claim 1 (currently amended): A light guide apparatus for enhancing light source utilization efficiency, comprising:

a light guide sheet;

a light coupling structure arranged on a surface of the light guide sheet and opposite to a light source, wherein the light coupling structure is formed with at least one groove extending along the light source, and wherein the light coupling structure is disposed substantially under the light source, and a distance from a geometrical center of the groove to the center of the light source is adjustable according to an amount of coupling lights needed; and

a light emerging structure disposed on ~~a~~the surface of the light guide sheet;

wherein light emitted by the light source can be introduced into the light guide sheet by the light coupling structure and can be drawn out of the light guide sheet by the light emerging structure, thereby enhancing light source utilization efficiency.

Claim 2 (currently amended): The light guide apparatus as claimed in claim 1, wherein the light guide sheet is made of a material having a refractive index greater than that of ~~the~~an outer environment where the light source ~~locates~~ is located.

Claim 3 (currently amended): The light guide apparatus as claimed in claim 2, wherein the material of the light guide sheet is a material selected from the group consisting of polycarbonate (PC), polyethylene terephthalate (PET) and ~~poly methyl methacrylate~~ polymethylmethacrylate (PMMA).

Claim 4 (currently amended): The light guide apparatus as claimed in claim 1, wherein ~~light coupling structure is formed with at least one groove extending along the light source, allowing the lights emitted by the light source to~~ can be introduced into the light guide sheet via the groove of the light coupling structure.

Claim 5 (original): The light guide apparatus as claimed in claim 4, wherein the groove is of a shape selected from the group consisting of a circular shape, triangle shape, polygon shape and irregular shape.

Claim 6 (currently amended): The light guide apparatus as claimed in claim 4, wherein the center of the light source is disposed at a geometrical center of ~~the~~ a section of the groove.

Claim 7 (canceled).

Claim 8 (original): The light guide apparatus as claimed in claim 1, wherein the light emerging structure comprises at least one micro structure for evenly distributing the light emitted by the light source.

Claim 9 (original): The light guide apparatus as claimed in claim 8, wherein the micro structure is a structure selected from the group consisting of a rhombic structure, a circular dot structure and an irregular structure.

Claim 10 (original): The light guide apparatus as claimed in claim 1, which is applicable to a backlight module.

Claim 11 (original): The light guide apparatus as claimed in claim 1, further comprising a reflecting surface provided at a side of the light guide apparatus against the light source, in order to act as an illuminating device.